Benchmarking for ____ Maintenance Operations

Jennifer Brandenburg, PE State Road Maintenance Engineer



What Is Benchmarking?



- Process of measuring condition and comparing it to customer expectations
- Looks at best practices and most effective ways to spend highway funds
- Continuous quality improvement
- Measures outcomes instead of processes

Why Benchmark?



- Learn from past successes, minimizing trial and error
- Improves customer satisfaction and the condition of highway system
- Reduces life cycle costs
- Able to deal more effectively with legislature and public
- Better able to allocate resources to most needed work
- Improves morale and job performance of employees

Who Are Our Customers?



- Legislature
- Public
- Divisions
- Central Units

Benchmarking Outcomes



- Total Asset Management
- Performance Based Standards
- Needs Based Funding



Developing a Rating Program for North Carolina

Pavement Condition Survey







Bridge Condition Survey







Maintenance Condition Survey



Bridge

- ✓ Decks
- ✓ Rails
- ✓ Expansion Joints
- √ Superstructure
- ✓ Substructure

Pavement

- √ Flexible
- √ Rigid

Roadway

- ✓ Low Shoulder
- ✓ High Shoulder
- ✓ Lateral Ditches
- ✓ Lateral Ditch

 Erosion

Roadside

- ✓ Mowing
- ✓ Brush and Tree
 Control
- ✓ Litter & Debris
- √ Slope
- ✓ Guardrail

<u>Drainage</u>

- ✓ Crossline Pipe
- ✓ Driveway Pipe
- ✓ Curb & Gutter
- ✓ Catch Basin &
 Drop Inlets
- ✓ Other Drainage Features

Environmental

- ✓ Turf Condition
- ✓ Miscellaneous Vegetation Management

Traffic Control Devices

- ✓ Traffic Signs
- ✓ Pavement Striping
- ✓ Words and Symbols
- ✓ Pavement Markers

Roadway Items (Shoulders and Ditches)








Element	Feature	Threshold Condition
Roadway pavement	Flexible Pavement	NCDOT Pavement Condition Survey
	Rigid Pavement	NCDOT Rigid Pavement Rating System
Unpaved Shoulders	Low Shoulder	Low ≥ 2 inches
& Ditches	High Shoulder	High ≥ 1 inch
	Lateral Ditches	Blocked > 50% and Not Functioning as designed
	Lateral Ditch Erosion	Eroded ≥ 1 ft
Drainage	Crossline Pipe	Blocked ≥ 50%, or Damaged
	Driveway Pipe	Blocked ≥ 50%, or Damaged
	Curb & Gutter	Blocked ≥ 2 in x 2 ft, or Damaged
	Catch Basin & Drop Inlet	Blocked \geq 25%, Damaged, or Grate Problem
	Other Drainage Features	Not Functioning as designed
Roadside	Mowing	Average Grass Height
	Brush and Tree Control	Within 15' above, 10' back of ditch/shoulder
	Litter & Debris	Number of Pieces ≥ Fist-Sized
	Slope	Failures ≥ 1ft wide
	Guardrail	Damaged, or Not Functioning as designed
Traffic Control Devices	Traffic Signs	Illegible, Missing, or Obliterated
	Pavement Striping	Worn, Missing, or Obliterated
	Words and Symbols	Damaged or Missing
	Pavement Markers	Worn, Missing, or Obliterated
Environmental	Turf Condition	Bare, Dead, Diseased, Distressed, or Weedy
	Misc. Vegetation Management	Uncontrolled Growth at Signs or Guardrail

Table 1 – Maintenance Elements Features and Threshold Conditions





Drainage









Element	Feature	Threshold Condition
Roadway pavement	Flexible Pavement	NCDOT Pavement Condition Survey
	Rigid Pavement	NCDOT Rigid Pavement Rating System
Unpaved Shoulders	Low Shoulder	Low ≥ 2 inches
& Ditches	High Shoulder	High ≥ 1 inch
	Lateral Ditches	Blocked ≥ 50% and Not Functioning as designed
	Lateral Ditch Erosion	Eroded ≥ 1 ft
Drainage	Crossline Pipe	Blocked ≥ 50%, or Damaged
	Driveway Pipe	Blocked ≥ 50%, or Damaged
	Curb & Gutter	Blocked ≥ 2 in x 2 ft, or Damaged
	Catch Basin & Drop Inlet	Blocked ≥ 25%, Damaged, or Grate Problem
	Other Drainage Features	Not Functioning as designed
Roadside	Mowing	Average Grass Height
	Brush and Tree Control	Within 15' above, 10' back of ditch/shoulder
	Litter & Debris	Number of Pieces \geq Fist-Sized
	Slope	Failures ≥ 1 ft wide
	Guardrail	Damaged, or Not Functioning as designed
Traffic Control Devices	Traffic Signs	Illegible, Missing, or Obliterated
	Pavement Striping	Worn, Missing, or Obliterated
	Words and Symbols	Damaged or Missing
	Pavement Markers	Worn, Missing, or Obliterated
Environmental	Turf Condition	Bare, Dead, Diseased, Distressed, or Weedy
	Misc. Vegetation Management	Uncontrolled Growth at Signs or Guardrail

Table 1 – Maintenance Elements Features and Threshold Conditions

Roadside









Element	Feature	Threshold Condition
Roadway pavement	Flexible Pavement	NCDOT Pavement Condition Survey
	Rigid Pavement	NCDOT Rigid Pavement Rating System
Unpaved Shoulders	Low Shoulder	Low≥2 inches
& Ditches	High Shoulder	High \ge 1 inch
	Lateral Ditches	Blocked ≥ 50% and Not Functioning as designed
	Lateral Ditch Erosion	Eroded ≥ 1 ft
Drainage	Crossline Pipe	Blocked ≥ 50%, or Damaged
	Driveway Pipe	Blocked ≥ 50%, or Damaged
	Curb & Gutter	Blocked ≥ 2 in x 2 ft, or Damaged
	Catch Basin & Drop Inlet	Blocked ≥ 25%, Damaged, or Grate Problem
	Other Drainage Features	Not Functioning as designed
Roadside	Mowing	Average Grass Height
	Brush and Tree Control	Within 15' above, 10' back of ditch/shoulder
	Litter & Debris	Number of Pieces <u>></u> Fist-Sized
	<mark>Slope</mark>	Failures <u>></u> 1ft wide
	<mark>Guardrail</mark>	Damaged, or Not Functioning as designed
Traffic Control Devices	Traffic Signs	Illegible, Missing, or Obliterated
	Pavement Striping	Worn, Missing, or Obliterated
	Words and Symbols	Damaged or Missing
	Pavement Markers	Worn, Missing, or Obliterated
Environmental	Turf Condition	Bare, Dead, Diseased, Distressed, or Weedy
	Misc. Vegetation Management	Uncontrolled Growth at Signs or Guardrail

Table 1 – Maintenance Elements Features and Threshold Conditions

Traffic Control Devices





Element	Feature	Threshold Condition
Roadway pavement	Flexible Pavement	NCDOT Pavement Condition Survey
	Rigid Pavement	NCDOT Rigid Pavement Rating System
Unpaved Shoulders	Low Shoulder	Low≥2 inches
& Ditches	High Shoulder	High \ge 1 inch
	Lateral Ditches	Blocked ≥ 50% and Not Functioning as designed
	Lateral Ditch Erosion	Eroded ≥ 1 ft
Drainage	Crossline Pipe	Blocked ≥ 50%, or Damaged
	Driveway Pipe	Blocked \geq 50%, or Damaged
	Curb & Gutter	Blocked ≥ 2 in x 2 ft, or Damaged
	Catch Basin & Drop Inlet	Blocked ≥ 25%, Damaged, or Grate Problem
	Other Drainage Features	Not Functioning as designed
Roadside	Mowing	Average Grass Height
	Brush and Tree Control	Within 15' above, 10' back of ditch/shoulder
	Litter & Debris	Number of Pieces \geq Fist-Sized
	Slope	Failures ≥ 1 ft wide
	Guardrail	Damaged, or Not Functioning as designed
Traffic Control	Traffic Signs	Illegible, Missing, or Obliterated
Devices	Pavement Striping	Worn, Missing, or Obliterated
	Words and Symbols	Damaged or Missing
	Pavement Markers	Worn, Missing, or Obliterated
Environmental	Turf Condition	Bare, Dead, Diseased, Distressed, or Weedy
	Misc. Vegetation Management	Uncontrolled Growth at Signs or Guardrail

Table 1 – Maintenance Elements Features and Threshold Conditions

Environmental









Element	Feature	Threshold Condition
Roadway pavement	Flexible Pavement	NCDOT Pavement Condition Survey
	Rigid Pavement	NCDOT Rigid Pavement Rating System
Unpaved Shoulders	Low Shoulder	Low≥2 inches
& Ditches	High Shoulder	High ≥ 1 inch
	Lateral Ditches	Blocked ≥ 50% and Not Functioning as designed
	Lateral Ditch Erosion	Eroded ≥ 1 ft
Drainage	Crossline Pipe	Blocked ≥ 50%, or Damaged
	Driveway Pipe	Blocked ≥ 50%, or Damaged
	Curb & Gutter	Blocked ≥ 2 in x 2 ft, or Damaged
	Catch Basin & Drop Inlet	Blocked ≥ 25%, Damaged, or Grate Problem
	Other Drainage Features	Not Functioning as designed
Roadside	Mowing	Average Grass Height
	Brush and Tree Control	Within 15' above, 10' back of ditch/shoulder
	Litter & Debris	Number of Pieces ≥ Fist-Sized
	Slope	Failures ≥ 1ft wide
	Guardrail	Damaged, or Not Functioning as designed
Traffic Control	Traffic Signs	Illegible, Missing, or Obliterated
Devices	Pavement Striping	Worn, Missing, or Obliterated
	Words and Symbols	Damaged or Missing
	Pavement Markers	Worn, Missing, or Obliterated
Environmental	Turf Condition	Bare, Dead, Diseased, Distressed, or Weedy
	Misc. Vegetation Mgm't.	Uncontrolled Growth at Signs or Guardrail

Table 1 – Maintenance Elements Features and Threshold Conditions

Large System / Large Sample Size (95% confidence level, <u>+</u> 6 %)

System	Mileage	Number of Samples	Level of Survey
Interstate	763	250	Statewide
Primary	11,081	3500	Division
Urban	7,607	3500	Division
Secondary	53,507	3500	Division
	Total Sample Size	10,750	

2002 Survey Findings








Pavements PCR = 83.5





Shoulders & Ditches Blocked ditches = 6%






Drainage
Other Features = 14%





Roadside Guardrail = 4%





Traffic Control

Pvm't Markers = 52%

Pvm't Markings = 12%





Environmental Misc. Vegt. Mgmt = 13%

What does that mean?













Maintenance Performance Measures - Primary

ELEMENT 1			Service Level					
Roadway Pavement		A	В	C	D	F	Acceptable	
Performance							Level of Service	
Activities	Condition Indicators	Measures	Threshold	Threshold	Threshold	Threshold	Threshold	
Pavement Maintenance	Pavement Condition Rating	PCR	98	93	86	70	<70	С

ELEMENT 2				Service Level				
Unpaved Shoulders and Ditches			A	В	C	D	F	Acceptable
		Porformance						re
Low Shoulder	A	В		C		D		F _
	101	- 0.7		00.4		4.4.0		4.40.4
	$\leq 1\%$	$\leq 5\%$		$\leq 8\%$		$\leq 11^{\circ}$	0	>11% _

ELEMENT 3								
Drainage			A	В	\mathbf{C}	D	F	Acceptable
Performance							Level of Service	
Activities	Condition Indicators	Measures	Threshold	Threshold	Threshold	Threshold	Threshold	Level of Service
Crossline Pipe	Blocked > 50%, or Damaged	EA	2%	7%	11%	15%	> 15%	С
Driveway Pipe	Blocked > 50%, or Damaged	EA	10%	15%	25%	35%	>35%	С
Ourb & Gutter	Blocked > 2 in x 2 ft, or Damaged	FT	2%	5%	7%	11%	>11%	С
Catch Basin & Drop Inlet	Blocked > 25%, Damaged, or Grate Problem	EA	2%	5%	8%	12%	>12%	С
Other Drainage Features	Not Functioning as designed	EA	2%	6%	9%	12%	>12%	С

Statewide Average - Primary System

	Level of Service				
Maintenance Activity	+ A -	+ B -	+ C -	+ D -	+ F -
Pavement					
Pavement					
Unpaved Shoulders and Ditches					
Low Shoulder					
High Shoulder					
Lateral Ditches					
Lateral Ditch Erosion					
Drainage					
Crossline Pipe					
Driveway Pipe					
Curb & Gutter					
Catch Basin & Drop Inlet					
Other Drainage Features					
Roadside					
Mowing					
Brush & Tree Control					
Litter & Debris					
Slope					
Guardrail					
Traffic Control Devices					
Traffic Signs					
Pavement Striping					
Words & Symbols					
Pavement Markers					
Environmental					
Turf Condition					
Misc. Vegetation Management					

Putting the Information in Context ____



Since the Highway Trust Fund was enacted:

1989

- 76,808 road miles
- 127,809 paved lane miles
- 16,104 miles of unpaved roads
- 16,900 structures
- 61.1 M sf bridge deck area

2003


- 78,347 road miles
- 155,960 paved lane miles
- 5,644 miles of unpaved roads
- 17,463 structures
- 72.3 M si bridge deck area

North Carolina State Highway System

Highway System Growth


(Paved Lane Miles)






Bridge System Growth

(Square Feet of Bridge Deck)



Highway System Usage

(Vehicle Miles Traveled)



Reporting Back to the Customers



North Carolina Department of Transportation



Condition Assessment & Funding Needs
for
North Carolina's Highway System



Report to the

Joint Legislative Transportation
Oversight Committee


January 14, 2003




Steve Varnedoe

Roadway Level of Service


(2002 Survey)



Performance Measure Trends (Roadway)



Performance Measure Trends (Bridge)




Target = 7


Results



History of Routine Maintenance Funding



History of Resurfacing Funding



Supplemental Maintenance Funds (Annual Basis)



- TIP Funding
- Senate Bill 1005
- NC Moving Ahead

Supplemental Maintenance Funds (Annual Basis)



TIP Funding

- Traffic System Operations \$ 13.0 million
- Positive Guidance Program \$ 6.6 million
- ITS Traffic Operations \$ 13.5 million
- Bridge Preservation Funds \$ 2.0 million

R-4701 + Maintenance Funds Traffic Systems Operations Program



Two funding sources - one charging scheme

Year 3: Total of \$18.5 million

\$5.5 million from Flexible "M" Funds

\$13.0 million from TIP R-4701

For operation and maintenance of traffic management devices

(signal equipment, LED's, Preventive Maintenance, Testing, Training, and ITS Devices)

- Allocation based on number of signals owned by DOT (including schedule C and schedule D agreements)
- Funds are managed centrally
- Report mechanism for Federal Audit

R-4067 Positive Guidance Program




- \$6.6 million per year
- Used for improving guidance and visibility on the primary roadway system
- Division's needs and priorities identified on an annual basis
- Chief Engineer's Office determines allocations with statewide consideration
- Report mechanism for Federal Audit

R-4049 Traffic Operations



- \$13.5 million
- Used for operation and maintenance of Incident Management and ITS Operations program
- Division's needs and priorities identified (by Divisions)
 on an annual basis (by Federal Fiscal Year)
- ITS Operations Unit determines allocations with statewide consideration
- Report mechanism for Federal audit

Estimated Total Funding this Fiscal Year



\$78.6 million!!!

Supplemental Maintenance Funds (Annual Basis)



- TIP Funding
- Senate Bill 1005
 - Traffic Mgmt. System Improvements \$ 15 million
 - Primary Pavement Preservation \$ 135 million

Impact of SB 1005 on Pavement Needs

- Targets major primary system corridors
- Approx. 5,500 lane miles will be strengthened and resurfaced
- Helps eliminate resurfacing backlog
- Reduces pavement needs

Supplemental Maintenance Funds (Annual Basis)



- TIP Funding
- Senate Bill 1005
- NC Moving Ahead
 - \$630 million for FY 2003-05 for highways
 - \$360 million for FY 2004-05

NC Moving Ahead



Funds used for preservation, modernization projects

- Safety enhancement
- Reduce congestion
- Improve traffic flow
- Reduce accidents
- Upgrade pavement widths and shoulder
- Extend pavement life
- Improve pavement smoothness
- Rehabilitate or replace deficient bridges

What's next?



- Connect condition data with MMS
- Implement new PMS
- New BMS
- Integrate Traffic Signal Management System
- Integrate real time GPS data

